



DUNBAR Heat Shrinkable Tubing

Part Number Cross Reference

DUNBAR P/N	AS230523/	Inventory	UL VW-1	TE/Raychem	Sumitomo	3M	Canusa	Alpha
------------	-----------	-----------	---------	------------	----------	----	--------	-------

Polyolefin Tubing

DUNBAR-1635F 2:1 Shrink Ratio, Flexible 135 °C, 600 V Rating UL/CSA & AS23053/5	/5 Class 1, 2, 3	Spools & 4' Lengths Large Inventory All Colors In Stock	Yes (except clear)	RNF-100 Versafit	SM12 B2 A2 SM35	FP-301 FP-301VW	CPX 100 PO135 CPX 876	FIT-221 FIT-221B
DUNBAR-1635F Y/G 2:1 Shrink Ratio, Flexible 135 °C, 600 V Rating		Spools & 4' Lengths	Yes	DCPT	B2(Y/G)		CPX 201	FIT-260
DUNBAR-1635S 2:1 Shrink Ratio, Semi-Rigid 135 °C, 600 V Rating AS23053/6	/6 Class 1 & 2	Spools & 4' Lengths Colors Available	No	CRN	B8 D	SR-350	CHM 140 HM 140	FIT-295
DUNBAR-3635 3:1 Shrink Ratio, Flexible 135 °C, 600 V Rating UL/CSA & AS23053/5	/5 Class 4	Spools: Most Colors Stocked All Colors Available	Yes (except clear)	RNF-300	SM23 B2(3X) A2(3X)	SFTW-203	CPX 300	FIT-321V
DUNBAR-4635 4:1 Shrink Ratio, Flexible 135 °C, 600 V Rating UL/CSA Rated		Spools: Black 4' Lengths: Black All Colors Available	Yes (except clear)	RP-4800	B2(4X)			FIT-421

Dual-Wall, Polyolefin Tubing

DUNBAR-2690NW 3:2 Shrink Ratio, Semi-Rigid 90 °C, 600 V Rating		No Stock 8 Week Lead Time	No		O2			
DUNBAR-1625W 2:1 Shrink Ratio, Flexible 125 °C, 600 V Rating UL & AS23053/4	/4 Class 2	Spools & 4' Lengths: Black 8 Week Lead Time	Yes (except clear)	TAT-125	O2B2 O2C SM24	EPS-200		FIT-750
DUNBAR-3625WS 3:1 Shrink Ratio, Semi-Rigid 135 °C, 600 V Rating UL & AS23053/4	/4 Class 1	4' Lengths: Black	Yes (except clear)	SCL	W5DL	MW		FIT-300
DUNBAR-3635W 3:1 Shrink Ratio, Flexible 135 °C, 600 V Rating UL & AS23053/4	/4 Class 3	4' Lengths & Spools (Spools through ½") Most Colors Stocked All Colors Available	Yes (except clear)	ATUM 3:1 DWP-125	W3B2 W3F2 W3C	EPS-300	CPA 300	FIT-321
DUNBAR-4635WS 4:1 Shrink Ratio, Semi-Rigid 135 °C, 600 V Rating UL Rated		4' Lengths Master Spools: (for cut to length) Standard Spools: Black & Clear	Yes (except clear)	ES-2000 ES-1000	SA2F	SMS TES	Splicemelt	
DUNBAR-4635WT 4:1 Shrink Ratio, Flexible 135 °C, 600 V Rating, Thin Wall UL Rated		4' Lengths & Spools: Black	Yes (except clear)		W3B2(4X)	EPS-400		
DUNBAR-4650WS 4:1 Shrink Ratio, Semi-Rigid 150 °C, 600 V Rating Fully Flame Retardant		4' Lengths Master Spools: (for cut to length) Standard Spools: Black	Yes (except clear)	FL-2500 SCT			CFRA	



Visit us at www.hstubing.com or contact Dunbar for any additional information

Oct



DUNBAR Heat Shrinkable Tubing Part Number Cross Reference

DUNBAR P/N	AS230523/	Inventory	UL VW-1	TE/Raychem	Sumitomo	3M	Canusa	Alpha
------------	-----------	-----------	---------	------------	----------	----	--------	-------

Medium & Heavy Wall Tubing

DUNBAR-CATV 3:1 Shrink Ratio, Flexible Adhesive Lined, Medium Wall 125 °C, 1000 V Rating		4' Lengths: Black	No	TCS SCTV		CCT	CFTV	
DUNBAR-CMWT-FR 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Medium Wall 125 °C, 1000 V Rating		4' Lengths: Black & Red	Yes	RMW SST BSTS			CFM	FIT-700
DUNBAR-PMWT-FR 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Medium Wall 125 °C, 1000 V Rating AS23053/15 C1 & C2	/15 Class 2	4' Lengths: Black & Red	Yes	SST-FR BSTS-FR		MDT		
DUNBAR-CHWT-FR 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Heavy Wall 125 °C, 1000 V Rating		4' Lengths: Black & Red	Yes	RHW SST BSTS			CFW	
DUNBAR-PHWT-FR 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Heavy Wall 125 °C, 1000 V Rating AS23053/15 C1 & C2	/15 Class 1	4' Lengths: Black & Red	Yes	SST-FR BSTS-FR HF		HDT	FCFW	
DUNBAR-BB10kV 3:1 Shrink Ratio Medium Wall 125 °C, 10,000 V Rating		No Stock 8 Week Lead Time	Yes					
DUNBAR-BB20kV 3:1 Shrink Ratio Medium Wall 125 °C, 20,000 V Rating		No Stock 8 Week Lead Time	Yes					
DUNBAR-BB35kV 3:1 Shrink Ratio Medium Wall 125 °C, 35,000 V Rating		No Stock 8 Week Lead Time	Yes					

Specialty Tubing

DUNBAR-CRFR 2:1 Shrink Ratio 121 °C, 600 V Rating AS23053/1	/1 Class 1 & 2	Spools: Black	Yes	NT-FR NT	R-10	NST	CNP 200	FIT-600
DUNBAR-1675 2:1 Shrink Ratio 175 °C, 600 V Rating UL & AS23053/8	/8	Spools: Clear 4' Lengths: Clear & Black Colors Available	Yes	Kynar RW-175	K	Kynar	CKN 175 HA 150	FIT-350
DUNBAR-DR150 2:1 Shrink Ratio 150 °C, 600 V Rating AS23053/16	/16	Spools: Black	Yes	DR-25	R120		CDR 625	
DUNBAR-FK150 2:1 Shrink Ratio 150 °C, 600 V Rating AS23053/18	/18 Class 2	Spools Only Black & Clear	Yes	RNF-150 (Black) RT-375 (Clear)				
DUNBAR-V200 2:1 Shrink Ratio 200 °C, 600 V Rating AS23053/13	/13	Spools Only Black	Yes	Viton RW-200	KH230 SM60 SM3-60	VTN-200	Deray- VT220	

Non-Shrinkable Polyolefin Tubing

DUNBAR-EIT-600 125 °C, 600 V Rating UL/CSA Rated		Limited Stock 8 Week Lead Time	Yes (except clear)					
---	--	-----------------------------------	-----------------------	--	--	--	--	--

Visit us at www.hstubing.com or contact Dunbar for any additional information

Oct