Heat Shrinkable Tubing
www.hstubing.com

Quick Selection Chart

Type	Product	Shrink Ratio	Recovery Temp (°C)	Operating Temp (°C)	Voltage (V)	Flame Retardant	Adhesive	UL File No.	MIL-Spec	Black	Brown	Red	Orange	Yellow	Green	Blue	Violet	Gray	White	Clear	Yellow/Green	Pink
Single Wall Polyolefin	DUNBAR-1635F	2:1	90	-55 ~ 135	600	VW-1 (Except clear)	No	E319303	AS23053/5 Class 1, 2 (clear) & 3											C		
	DUNBAR-1635F Y/G	2:1	90	-55 ~ 135	600	VW-1	No	E319303	Commercial													
	DUNBAR-DC-221	2:1	90	-55 ~ 125	600	VW-1 (Except clear)	No	E319303	Commercial											C		
	DUNBAR-DC-M221	2:1	90	-55 ~ 135	600	VW-1 (Except clear)	No	E319303	Commercial											C		
	DUNBAR-1635S	2:1	130	-55 ~ 135	600	VW-1	No	N/A	AS23053/6											C		
	DUNBAR-3635	3:1	90	-55 ~ 135	600	VW-1 (Except clear)	No	E319303	AS23053/5 Class 4											C		
	DUNBAR-DC-321	3:1	90	-55 ~ 125	600	VW-1	No	N/A	Commercial											C		
	DUNBAR-4635	4:1	90	-55 ~ 135	600	VW-1	No	E319303	Commercial											C		
Dual Wall Polyolefin (Adhesive Lined)	DUNBAR-1625W	2:1	120	-55 ~ 125	600	VW-1	Yes	E319314	AS23053/4 Class 2											C		
	DUNBAR-2690NW	3:2	120	-35 ~ 90	600	No	Yes	N/A	Commercial													
	DUNBAR-2690NW-LT	3:2	80	-35 ~ 90	600	No	Yes	N/A	Commercial													
	DUNBAR-3625WS	3:1	125	-55 ~ 125	600	VW-1	Yes	E319314	AS23053/4 Class 1											C		
	DUNBAR-3635W	3:1	120	-55 ~ 135	600	VW-1	Yes	E319314	AS23053/4 Class 3											C		
	DUNBAR-DC-321A	3:1	120	-55 ~ 125	600	VW-1	Yes	E319303	Commercial											C		
	DUNBAR-DC-M321A	3:1	120	-55 ~ 135	600	VW-1	Yes	E319303	Commercial											C		
	DUNBAR-4635WS	4:1	130	-55 ~ 130	600	VW-1	Yes	E319314	Commercial											C		
	DUNBAR-4635WT	4:1	120	-55 ~ 135	600	VW-1	Yes	E319314	Commercial											C		
	DUNBAR-4650WS	4:1	130	-55 ~ 150	600	VW-1	Yes	E319314	Commercial											C		
Medium & Heavy Wall Tubing	DUNBAR-CATV	3:1	120	-55 ~ 125	1000	No	Yes	E319303	Commercial													
	DUNBAR-CMWT-FR	3:1	120	-55 ~ 125	1000	VW-1	Yes	E319303	Commercial													
	DUNBAR-CHWT-FR	3:1	120	-55 ~ 125	1000	VW-1	Yes	E319303	Commercial													
	DUNBAR-PMWT-FR	3:1	120	-55 ~ 125	1000	VW-1	Yes	E319303	AS23053/15 Class 2													
	DUNBAR-PHWT-FR	3:1	120	-55 ~ 125	1000	VW-1	Yes	E319303	AS23053/15 Class 1													

Rev. April 2024

Certifications:

ISO 9001:2015
AS9100 Rev D Registered

Underwriters Laboratories Inc.
TUV (R86603)

RoHS

REACH

ABS
Certificate Type of Approval

DNV
Type Approval Certificate

1302 Champion Circle
Carrollton, TX 75006

Tel: (469) 568-0800

Heat Shrinkable Tubing
www.hstubing.com

Quick Selection Chart

Type	Product	Shrink Ratio	Recovery Temp (°C)	Operating Temp (°C)	Voltage (V)	Flame Retardant	Adhesive	UL File No.	MIL- Spec	Available Colors													
										Black	Brown	Red	Orange	Yellow	Green	Blue	Violet	Gray	White	Clear	Yellow/Green	Rust
Specialty Tubing	DUNBAR-FK150	2:1	150	-55 ~ 150	600	VW-1	No	E319303	AS23053/18 Class 2	■										C		
	DUNBAR-1675	2:1	175	-55 ~ 175	600	VW-1	No	E319303	AS23053/8	■										C		
	DUNBAR-CRFR	2:1	135	-70 ~ 121	600	VW-1	No	N/A	AS23053/1	■												
	DUNBAR-DR150	2:1	135	-75 ~ 150	600	VW-1	No	N/A	AS23053/16	■												
	DUNBAR-V200	2:1	100	-40 ~ 200	600	VW-1	No	N/A	AS23053/13	■												
	DUNBAR-EV2500	2:1	80	-55 ~ 135	2500	VW-1	No	N/A	Commercial				■									
	DUNBAR-BB10kV	2.5:1	120	-40 ~ 125	10000	VW-1	No	N/A	Commercial													■
	DUNBAR-BB20kV	2.5:1	120	-40 ~ 125	20000	VW-1	No	N/A	Commercial													■
	DUNBAR-BB35kV	2.5:1	120	-40 ~ 125	35000	VW-1	No	N/A	Commercial													■
	DUNBAR-WFHS	2:1	80	-40 ~ 125	N/A	FMVSS 302	No	N/A	Commercial	■			■									
	DUNBAR-DC-EC	2:1	130	-55 ~ 110	N/A	N/A	Yes	N/A	Commercial	■												
Teflon	DUNBAR-FEP1.3	1.3:1	210 ~ 221	-75 ~ 200	2000	V-0	No	N/A	Commercial											C		
	DUNBAR-FEP1.6	1.6:1	210 ~ 221	-75 ~ 200	2000	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE2H	2:1	350	-75 ~ 260	1400	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE2S	2:1	350	-75 ~ 260	1400	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE2T	2:1	350	-75 ~ 260	1400	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE2L	2:1	350	-75 ~ 260	1400	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE4	4:1	350	-75 ~ 260	1400	V-0	No	N/A	Commercial											C		
	DUNBAR-ETFE1.5	1.5:1	175	-75 ~ 150	2000	V-0	No	N/A	Commercial											C		
	DUNBAR-FEP Roll Cover	1.25:1	175	-75 ~ 200	2000	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE/FEP (SW)	1.4:1 ~ 3:1	360	-75 ~ 200	2000	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE AWG (HW)	0:0	N/A	-75 ~ 260	1400	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE AWG (SW)	0:0	N/A	-75 ~ 260	1400	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE AWG (TW)	0:0	N/A	-75 ~ 260	1400	V-0	No	N/A	Commercial											C		
	DUNBAR-PTFE AWG (LW)	0:0	N/A	-75 ~ 260	1400	V-0	No	N/A	Commercial											C		

Rev. April 2024

Certifications:

ISO 9001:2015
AS9100 Rev D Registered

Underwriters Laboratories Inc.
TUV (R86603)

RoHS

REACH

ABS
Certificate Type of Approval

DNV
Type Approval Certificate

1302 Champion Circle
Carrollton, TX 75006

Tel: (469) 568-0800