



# DUNBAR Heat Shrinkable Tubing

## Part Number Cross Reference

DUNBAR P/N	AS230523/	Inventory	UL VW-1	TE/Raychem	Sumitomo	3M	Canusa	Alpha
------------	-----------	-----------	---------	------------	----------	----	--------	-------

### Polyolefin Tubing

<b>DUNBAR-1605</b> 2:1 Shrink Ratio, Flexible 105 °C, 600 V Rating UL Rated		No Stock Use 1635F Exceeds all Ratings	Yes		C2 A4		CPX 51	
<b>DUNBAR-1625</b> 2:1 Shrink Ratio, Flexible 125 °C, 600 V Rating UL/CSA Rated		No Stock Use 1635F Exceeds all Ratings	Yes		F2 F32 F2(Z)	CP-221		FIT-221V
<b>DUNBAR-1635F</b> 2:1 Shrink Ratio, Flexible 135 °C, 600 V Rating UL/CSA & AS23053/5	/5 Class 1, 2, 3	Spools & 4' Lengths Large Inventory All Colors In Stock	Yes (except clear)	RNF-100 Versafit	SM12 B2 A2 SM35	FP-301 FP-301VW	CPX 100 PO135 CPX 876	FIT-221 FIT-221B
<b>DUNBAR-1635F Y/G</b> 2:1 Shrink Ratio, Flexible 135 °C, 600 V Rating		Spools & 4' Lengths	Yes	DCPT	B2(Y/G)		CPX 201	FIT-260
<b>DUNBAR-1635S</b> 2:1 Shrink Ratio, Semi-Rigid 135 °C, 600 V Rating AS23053/6	/6 Class 1 & 2	Spools & 4' Lengths Colors Available	Yes (except clear)	CRN	B8 D	SR-350	CHM 140 HM 140	FIT-295
<b>DUNBAR-3635</b> 3:1 Shrink Ratio, Flexible 135 °C, 600 V Rating UL/CSA & AS23053/5	/5 Class 4	Spools: Most Colors Stocked All Colors Available	Yes (except clear)	RNF-300	SM23 B2(3X) A2(3X)	SFTW-203	CPX 300	FIT-321V
<b>DUNBAR-4635</b> 4:1 Shrink Ratio, Flexible 135 °C, 600 V Rating UL/CSA Rated		Spools: Black 4' Lengths: Black All Colors Available	Yes (except clear)	RP-4800	B2(4X)			FIT-421

### Specialty Tubing

<b>DUNBAR-CRFR</b> 2:1 Shrink Ratio 121 °C, 600 V Rating AS23053/1	/1 Class 1 & 2	Spools: Black	Yes	NT-FR NT	R-10	NST	CNP 200	FIT-600
<b>DUNBAR-1675</b> 2:1 Shrink Ratio 175 °C, 600 V Rating UL & AS23053/8	/8	Spools: Clear 4' Lengths: Clear & Black Colors Available	Yes	Kynar RW-175	K	Kynar	CKN 175 HA 150	FIT-350
<b>DUNBAR-3675</b> 3:1 Shrink Ratio 175 °C, 600 V Rating UL Rated		No Stock 8 Week Lead Time	Yes					
<b>DUNBAR-DRET</b> 2:1 Shrink Ratio 120 °C, 600 V Rating		**Discontinued: Use DR150 For Higher Temperature Rating	Yes	DR-25	R120		CDR 625	
<b>DUNBAR-DR150</b> 2:1 Shrink Ratio 150 °C, 600 V Rating AS23053/16	/16	Spools: Black	Yes	DR-25	R120		CDR 625	
<b>DUNBAR-FK150</b> 2:1 Shrink Ratio 150 °C, 600 V Rating AS23053/18	/18 Class 2	Spools Only Black & Clear	Yes	RNF-150 (Black) RT-375 (Clear)				
<b>DUNBAR-V200</b> 2:1 Shrink Ratio 200 °C, 600 V Rating AS23053/13	/13	Spools Only Black	Yes	Viton RW-200	KH230 SM60 SM3-60	VTN-200	Deray- VT220	

### Non-Shrinkable Polyolefin Tubing

<b>DUNBAR-EIT-600</b> 125 °C, 600 V Rating UL/CSA Rated		Very Limited Stock 8 Week Lead Time	Yes (except clear)					
---	--	--	-----------------------	--	--	--	--	--

Visit us at [www.hstubing.com](http://www.hstubing.com) or contact Dunbar for any additional information

**May 2024**



## DUNBAR Heat Shrinkable Tubing Part Number Cross Reference

DUNBAR P/N	AS230523/	Inventory	UL VW-1	TE/Raychem	Sumitomo	3M	Canusa	Alpha
------------	-----------	-----------	---------	------------	----------	----	--------	-------

### Dual-Wall, Polyolefin Tubing

<b>DUNBAR-2690NW</b> 3:2 Shrink Ratio, Semi-Rigid 90 °C, 600 V Rating		No Stock 8 Week Lead Time	No		O2			
<b>DUNBAR-1625W</b> 2:1 Shrink Ratio, Flexible 125 °C, 600 V Rating UL & AS23053/4	/4 Class 2	Spools & 4' Lengths: Black 8 Week Lead Time	Yes (except clear)	TAT-125	O2B2 O2C SM24	EPS-200		FIT-750
<b>DUNBAR-3625WS</b> 3:1 Shrink Ratio, Semi-Rigid 135 °C, 600 V Rating UL & AS23053/4	/4 Class 1	4' Lengths: Black	Yes (except clear)	SCL	W5DL	MW		FIT-300
<b>DUNBAR-3635W</b> 3:1 Shrink Ratio, Flexible 135 °C, 600 V Rating UL & AS23053/4	/4 Class 3	4' Lengths & Spools (Spools through 1/2") Most Colors Stocked All Colors Available	Yes (except clear)	ATUM 3:1 DWP-125	W3B2 W3F2 W3C	EPS-300	CPA 300	FIT-321
<b>DUNBAR-4635WS</b> 4:1 Shrink Ratio, Semi-Rigid 135 °C, 600 V Rating UL Rated		4' Lengths Master Spools: (for cut to length) Standard Spools: Black & Clear	Yes (except clear)	ES-2000 ES-1000	SA2F	SMS TES	Splicemelt	
<b>DUNBAR-4635WT</b> 4:1 Shrink Ratio, Flexible 135 °C, 600 V Rating, Thin Wall UL Rated		4' Lengths & Spools: Black	Yes (except clear)		W3B2(4X)	EPS-400		
<b>DUNBAR-4650WS</b> 4:1 Shrink Ratio, Semi-Rigid 150 °C, 600 V Rating Fully Flame Retardant		4' Lengths Master Spools: (for cut to length) Standard Spools: Black	Yes (except clear)	FL-2500 SCT			CFRA	

### Medium & Heavy Wall Tubing

<b>DUNBAR-CATV</b> 3:1 Shrink Ratio, Flexible Adhesive Lined, Medium Wall 125 °C, 1000 V Rating		4' Lengths: Black	No	TCS SCTV		CCT	CFTV	
<b>DUNBAR-CMWT</b> 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Medium Wall 125 °C, 1000 V Rating		4' Lengths: Black & Red	Yes	RMW SST BSTS			CFM	FIT-700
<b>DUNBAR-PMWT-FR</b> 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Medium Wall 125 °C, 1000 V Rating AS23053/15 C1 & C2	/15 Class 1 & 2	4' Lengths: Black & Red	Yes	SST-FR BSTS-FR		MDT		
<b>DUNBAR-CHWT</b> 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Heavy Wall 125 °C, 1000 V Rating		4' Lengths: Black & Red	Yes	RHW SST BSTS			CFW	
<b>DUNBAR-PHWT-FR</b> 3:1 Shrink Ratio, Semi-Rigid Adhesive Lined, Heavy Wall 125 °C, 1000 V Rating AS23053/15 C1 & C2	/15 Class 1 & 2	4' Lengths: Black & Red	Yes	SST-FR BSTS-FR HF		HDT	FCFW	
<b>DUNBAR-BB10kV</b> 3:1 Shrink Ratio Medium Wall 125 °C, 10,000 V Rating		No Stock 8 Week Lead Time	Yes					
<b>DUNBAR-BB20kV</b> 3:1 Shrink Ratio Medium Wall 125 °C, 20,000 V Rating		No Stock 8 Week Lead Time	Yes					
<b>DUNBAR-BB35kV</b> 3:1 Shrink Ratio Medium Wall 125 °C, 35,000 V Rating		No Stock 8 Week Lead Time	Yes					

Visit us at [www.hstubing.com](http://www.hstubing.com) or contact Dunbar for any additional information

**May 2024**